

Worksheet: Strip Doors

Number of Doors Required: _____

NOTE: All doors must have the same specifications as given below.
Please complete additional worksheets if specifications vary.

Opening Size: Width: _____ Height: _____

Environment: (check one)

- Inside Exposed to the outside

Mounting Style: (check one)

- In-jamb (for mounting underside of door lintel or on ceilings)
 Face of wall (where no door is present)

Mounting System (hardware):

- Universal mount—designed for in-jamb or face of wall

Strip Material: (check one)

- Standard
 Low temperature/USDA (-20° to + 100° F)
 Weld
 DayGlow (orange)

Strip Style: (check one)

- Flat Ribbed (for high-traffic areas/material handling vehicle passage)

Strip Width and Overlap: (check one)

- 6-inch width, 2/3 overlap
 8-inch width, 1/2 overlap
 8-inch width, full overlap - see note
 12-inch width, 2/3 overlap
 12-inch width, full overlap - see note
 16-inch width, 1/2 overlap
 16-inch width, full overlap - see note

Note: Full strip overlap is usually used for doors exposed to the outside or door ways with a high pressure differential.

Additional strip widths and overlaps are available upon request.

Additional information: _____

Strip Doors

Contact Name: _____

Company Name: _____

Phone: _____

Fax: _____

Email: _____

Telephone: 1-800-446-7325 or 1-804-743-1218

Fax: 1-800-448-2908 or 1-804-743-3413

Email: weatherseal@sealeze.com



ISO 9001 Certified

8000 Whitepine Rd.
Richmond, VA 23237
www.sealeze.com