
Door Jamb

Worksheet [R. 12.2014]



For jamb seals, refer to Sealeze worksheet WSDS.

Contact Name:
Company Name:
Phone:
Fax:
Email:

DOOR JAMB KITS

Product Code	Holder Color	Holder Angle	Door Size	
			ft	m
J135CLA04BL17	clear (silver)	35°	3 x 7	0.9144 x 2.1336
J135DUR04BL17	dark brown	35°	3 x 7	0.9144 × 2.1336
JR40CLA04BL17	clear (silver)	40°	3 x 7	0.9144 x 2.1336
J140CLA04BL17	clear (silver)	40°	3 x 7	0.9144 × 2.1336
J140DUR04BL17	dark brown	40°	3 x 7	0.9144 × 2.1336
J135CLA04BL18	clear (silver)	35°	4 x 7	1.2192 x 2.1336
J135DUR04BL18	dark brown	35°	4 x 7	1.2192 x 2.1336
JR40CLA04BL18	clear (silver)	40°	4 x 7	1.2192 x 2.1336
J140CLA04BL18	clear (silver)	40°	4 x 7	1.2192 x 2.1336
J140DUR04BL18	dark brown	40°	4 x 7	1.2192 x 2.1336
J135CLA04BL20	clear (silver)	35°	6 x 7	1.8288 x 2.1336
J135DUR04BL20	dark brown	35°	6 x 7	1.8288 x 2.1336
JR40CLA04BL20	clear (silver)	40°	6 x 7	1.8288 x 2.1336
J140CLA04BL20	clear (silver)	40°	6 x 7	1.8288 x 2.1336
J140DUR04BL20	dark brown	40°	6 x 7	1.8288 x 2.1336

Refer to the appropriate Sealeze Worksheet for Door Sweeps.

Specifications

- 1. Measure the width of the top of the door:
- 2. Measure the length of door side:

3. Determine what color or finish you want for the brush holder:

gold silver dark brown

- 4. Determine the holder angle for best fit:
- 5. Select the proper Door Jamb Kit Product No.: _____

Quantity:

JR40 and J140 kits come with screw slots for after-installation adjustment. J135 kits have counter-sunk screw holes for a neat, flush finish. Fastners and installation instructions are provided with all kits.



Sealeze Nylon Therm-L-Brush® up to 4 in. long are UL labeled for use on 3-hour fire doors.

